

CLAIMS

What is claimed is:

1. An optical add-drop multiplexing (OADM) device comprising:

5 a wavelength adapter module for transforming unstabilized non-monochromatic or monochromatic light energy into one or more channels of stabilized monochromatic light energy having one or more predefined wavelength regions; and

10 a filter module for at least one of dropping, adding, and recombining one or more channels of stabilized monochromatic light energy having one or more predefined wavelength regions, whereby information traffic carried by an optical waveguide is substantially increased.

15 2. The OADM device of claim 1, wherein the wavelength adapter module further comprises:

a light detector for converting light energy into electrical energy; and

a laser device for outputting modulated light energy in accordance with said electrical energy.

20 3. The OADM device of claim 1, wherein the wavelength adapter module further comprises an optical feedback assembly coupled to an optical waveguide.

4. The OADM device of claim 3, wherein the optical feedback assembly comprises a Bragg grating.

25 3-5. The OADM device of claim 2, wherein laser device comprises a laser diode initially producing unstabilized non-monochromatic or monochromatic light energy at approximately 1310 or 1550 nm wavelength region prior to stabilization.

~~4.~~ 6. The OADM device of claim 1, wherein the filter module comprises:

a planar light guide circuit;

a plurality of filters disposed adjacent to said planar light guide circuit; and

a plurality of optical waveguides connected to said planar light guide circuit.

⁵ ~~5.~~ 7. The OADM device of claim ~~6.~~ ^{4.}, wherein each filter comprises a thin film interference filter.

8. The OADM device of claim 1, ~~wherein the OADM device is part of a SONET~~
10 optical network.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

9. An optical amplifier comprising:

a light detector for converting light energy into electrical energy; and

a laser device for outputting modulated light energy in accordance with said electrical energy.

5

10. The optical amplifier of claim 9, further comprising a optical feedback assembly coupled to an optical waveguide.

10

11. The optical amplifier of claim 10, wherein the optical feedback assembly comprises a Bragg grating.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

6. ~~12.~~ An optical network comprising:
a SONET network; and
a plurality of optical add-drop multiplexing (OADM) devices connected to a plurality of SONET network terminals;

5 each OADM device comprising:

a wavelength adapter module for transforming unstabilized non-monochromatic or monochromatic light energy into one or more channels of stabilized monochromatic light energy having one or more predefined wavelength regions; and

10 a filter module for at least one of dropping, adding, and recombining one or more channels of stabilized monochromatic light energy having one or more predefined wavelength regions.

7. ~~13.~~ The optical network of claim ~~12~~, wherein the SONET network comprises a protection switching scheme that operates irrespective of the plurality of OADM devices.

8. ~~14.~~ The optical network of claim ~~12~~, wherein each OADM balances information flow by propagating light energy containing information channels through respective optical waveguides connected to each OADM device, whereby a number of information routes between at least one of users and central offices are increased.

9. ~~15.~~ The optical network of claim ~~12~~, wherein the unstabilized non-monochromatic or monochromatic light energy is light energy propagating according to a predefined network protocol.

10. ~~16.~~ The optical network of claim ~~15~~, wherein the unstabilized non-monochromatic or monochromatic light energy is light energy propagating according to a synchronous optical network (SONET) protocol.

~~17.~~ The optical network of claim ~~12~~^{6.}, wherein the wavelength adapter module further comprises:

a light detector for converting light energy into electrical energy; and

a laser device for outputting modulated light energy in accordance with said
5 electrical energy.

~~14.~~ The optical network of claim ~~12~~^{6.}, wherein the wavelength adapter module further comprises a optical feedback assembly coupled to an optical waveguide.

~~15.~~ The optical network of claim ~~18~~^{14.}, wherein the optical feedback assembly comprises a Bragg grating.

~~12.~~ The optical network of claim ~~17~~¹¹, wherein laser device comprises a laser diode initially producing unstabilized non-monochromatic or monochromatic light energy at
15 approximately 1310 or 1550 nm wavelength region prior to stabilization.

~~13.~~ The optical network of claim ~~17~~¹¹, wherein laser device comprises a Fabry-Perot laser initially producing unstabilized non-monochromatic or monochromatic light energy at approximately 1310 or 1550 nm wavelength region prior to stabilization,
20 said Fabry-Perot laser producing stabilized light energy at a predefined wavelength region within a spectral grid, said grid comprises a portion of either said 1310 or 1550 nm wavelength region.

~~16.~~ The optical network of claim ~~12~~^{6.}, wherein the filter module comprises:
25 a planar light guide circuit;
a plurality of filters disposed adjacent to said planar light guide circuit; and
a plurality of optical waveguides connected to said planar light guide circuit.

~~17.~~ The optical network of claim ~~22~~^{16.}, wherein each filter comprises a thin film
30 interference filter.

26. A method for increasing a number of information channels carried by an optical waveguide, comprising the steps of:

transforming unstabilized non-monochromatic or monochromatic light energy into a plurality of channels of monochromatic light energy having one or more predefined wavelength regions with an optical add-drop multiplexing (OADM) device;

dropping one or more channels of stabilized monochromatic light energy having one or more predefined wavelength regions with the OADM device;

adding one or more channels of stabilized monochromatic light energy having one or more predefined wavelength regions with the OADM device; and

recombining one or more channels of stabilized monochromatic light energy having predefined wavelength regions with the OADM device, whereby information traffic carried by an optical waveguide is substantially increased.

27. The method of 26, further comprising the step of connecting the OADM device between a terminal and an optical network.

28. The method of claim 26, wherein the transforming step further comprises the steps of:

converting the light energy into electrical energy;
modulating a laser device with the electrical energy; and
outputting light energy from the laser device.

29. The method of claim 28, wherein the converting step comprises channeling the light energy into the input of a light detector.

30. The method of claim 28, wherein the converting step comprises channeling the light energy into the input of a photodetector.

31. The method of claim 28, wherein the modulating step comprises modulating a laser diode.

32. The method of claim 31, wherein the laser diode initially produces unstabilized non-monochromatic or monochromatic light energy at approximately 1310 or 1550 nm wavelength region before being stabilized.

5 33. The method of claim 28, further comprising the steps of:

filtering the light energy generated by the laser device;

reflecting filtered light energy of a predefined wavelength region back into the laser device;

stabilizing the laser device with the filtered light energy; and

10 outputting stabilized monochromatic light energy of the predefined wavelength region from the laser device matching the wavelength region of the reflected filtered light energy. *Q*

15 34. The method of claim 33, wherein the filtering and reflecting steps comprise filtering and reflecting the light energy with a grating.

35. The method of claim 34, wherein the grating filter comprises a Bragg grating.

20 36. The method of claim 26, wherein the dropping and adding steps further comprise the step of transmitting at least one of non-monochromatic and monochromatic light energy through a planar light guide circuit.

37. The method of claim 36, wherein the transmitting step includes cascading the light energy through a planar light guide circuit, said cascading comprising the steps of:

5 filtering at least one of the non-monochromatic and monochromatic light energy within the planar light guide circuit;

propagating filtered stabilized monochromatic light energy away from the planar light guide circuit;

propagating stabilized monochromatic light energy to the planar light guide circuit; and

10 reflecting the stabilized monochromatic light energy between one or more filters disposed within the planar light guide circuit.

38. The method of claim 37, wherein the filtering step further comprises filtering the stabilized monochromatic light energy with one or more thin film interference filters.

15 39. The method of claim 37, wherein the step of propagating filtered stabilized monochromatic light energy away from the planar light guide circuit further comprises channeling the filtered stabilized monochromatic light energy within an optical waveguide.

20 40. The method of claim 37, wherein the step of propagating stabilized monochromatic light energy to the planar light guide circuit further comprises channeling the stabilized monochromatic light energy within an optical waveguide.

25 41. The method of claim 26, further comprising the step of overlaying a plurality OADM devices on an optical network to increase the number channels carried by the optical network.

30 42. The method of claim 26, further comprising the step of overlaying a plurality OADM devices on a synchronous optical network (SONET) to increase the number channels carried by the optical network.

43. The method of claim 42, wherein the SONET network comprises a protection switching scheme that operates irrespective of the plurality of OADM devices.

5 44. The method of claim 32, wherein each OADM balances information flow by propagating light energy containing information channels through respective optical waveguides connected to each OADM device, whereby a number of information routes between at least one of users and central offices are increased.

10 45. The method of claim 26, wherein the unstabilized non-monochromatic or monochromatic light energy is light energy propagating according to a network protocol.

15 46. The method of claim 45, wherein the unstabilized non-monochromatic or monochromatic light energy is light energy propagating according to a synchronous optical network protocol.

47. A method for amplifying light energy comprising the steps of:

converting unstabilized or stabilized light energy into electrical energy;
modulating a laser device with the electrical energy; and
outputting light energy from the laser device.

5

48. The method of claim 47, further comprising the steps of:

filtering the light energy generated by the laser device;
reflecting the filtered light energy of a predefined wavelength region back into
the laser device;
stabilizing the laser device with the reflected light energy; and
outputting stabilized monochromatic light energy of the predefined
wavelength region from the laser device matching the wavelength region of the
reflected filtered light energy.

10

49. The method of claim 47, wherein the converting step comprises channeling the
light energy into the input of a light detector.

15

50. The method of claim 47, wherein the converting step comprises channeling the
light energy into the input of a photodetector.

20

51. The method of claim 47, wherein the modulating step comprises modulating a
laser diode.

52. The method of claim 47, wherein the laser diode initially produces unstabilized
non-monochromatic or monochromatic light energy at approximately 1310 or 1550
nm wavelength region before being stabilized.

25

53. The method of claim 47, further comprising the step of propagating single mode
light energy outputted by said laser device within a planar lightguide circuit.

30

54. The method of claim 48, further comprising the steps of:
outputting the light energy from a facet of a semiconductor gain medium; and
propagating the light energy through a single mode waveguided pathway
before and after the reflecting step.
- 5 55. A method for amplifying monochromatic light energy of an optical network,
comprising:
propagating monochromatic light energy having a plurality of predefined
wavelength regions into a filter module;
filtering the monochromatic light energy into separate wavelength regions
10 with the filter module;
feeding the separated light energy into a semiconductor device;
amplifying the separated light energy with the semiconductor device; and
feeding the amplified light energy back into the filter module.
- 15 56. The method of claim 55, wherein the semiconductor device comprises an active
gain medium that undergoes stimulated emissions.
57. The method of claim 55, wherein the semiconductor device comprises a laser
diode, the amplifying step further comprises the steps of:
20 converting light energy into electrical energy; and
outputting light energy from the laser diode.
58. The method of claim 55, further comprising the steps of:
filtering the light energy generated by the laser diode;
25 reflecting some filtered light energy of one of the plurality of predefined
wavelength regions back into the laser diode;
stabilizing the laser diode with the filtered light energy; and
outputting monochromatic light energy at the one of the plurality of
predefined wavelength regions from the laser diode matching the wavelength region
30 of the reflected filtered light energy.

further comp
 ough a segm
 2

add r_2

[illegible]